

DRAG BLOCK TUBING ANCHOR/CATCHER

The **Drag Block Tubing Anchor/Catcher** (DB Anchor) is a retrievable positive-action tubing anchor designed to hold the tubing string in tension or compression. It has drag blocks to allow the anchor to be run deeper than conventional drag spring anchors. The anchor prevents movement of the tubing during pumping strokes; and holds it stationary if it should part. The use of a tension tubing anchor increases pump efficiency, reduces rod and tubing wear, and keeps tubing and rods from falling into the well in case of a part.

Special Features

- Enclosed slips
- Rotational release or shear release
- Safety release value easily adjusted



Product Specifications

Casing		Recommended Hole Size (inches)	Gage OD (inches)	Max OD (inches)	Tool ID (inches)	Thread Connections Box Up / Pin Down	Part Number
Size (inches)	Weight (lbs/ft)						
4-1/2	9.5 - 13.5	3.920 - 4.090	3.750	-	1.94	2-3/8 EUE	32545
5-1/2	13.0 - 20.0	4.778 - 5.044	4.500	4.640 ¹	2.00	2-3/8 EUE	32555
					2.44	2-7/8 EUE	32556
7	17.0 - 32.0	6.094 - 6.538	5.750	5.854 ¹	2.50	2-7/8 EUE	32570
					3.00	3-1/2 EUE	32573
7-5/8	24.0 - 39.0	6.625 - 7.025	6.400	6.404 ¹	2.50	2-7/8 EUE	32575
8-5/8	24.0 - 40.0	7.725 - 8.097	7.500	7.687 ¹	4.00	4-1/2 EUE	32585
9-5/8	32.3 - 53.5	8.535 - 9.001	8.250	-	3.00	3-1/2 EUE	32595-XBAE
					4.00	4-1/2 EUE	32595

¹ Maximum OD is across retracted drag blocks.

NOTE: All pricing includes standard Nitrile trim. Other sizes and connections available upon request.

Anchors