

GV CUP PACKER

The **Type GV Cup Packer** is an economical means of isolating casing leaks and depleted zones and is also a production or injection packer for low pressure applications. Depending on application, this packer can be run with cups opposed or in the same direction. This packer is also available with packing element back-up rings for higher pressure

applications and comes in a full range of tubing and casing sizes in two-cup or four-cup models.

Special Features

- Economic design
- Cup direction option
- Tubing size options

Product Specifications

Casing		Recommended Hole Size (inches)	Tool OD (inches)	Tool ID (inches)	Thread Connections Box Up / Pin Down	Part Number
Size (inches)	Weight (lbs/ft)					
3-1/2	9.2 - 10.3	2.922 - 2.992	2.810	1.50	1.900 NUE	43935
4-1/2	9.5 - 13.5	3.920 - 4.090	3.750	2.00	2-3/8 EUE	43945
				2.50	2-7/8 EUE	43946
	15.1	3.826	3.650	2.00	2-3/8 EUE	43947
5	13.0 - 15.0	4.408 - 4.494	4.250	2.00	2-3/8 EUE	43951
	18.0	4.276	4.130	2.00	2-3/8 EUE	43950
5-1/2	13.0 - 20.0	4.778 - 5.044	4.625	3.00	3-1/2 EUE	43953
	14.0 - 20.0	4.778 - 5.012	4.625	2.50	2-7/8 EUE	43956
	17.0 - 20.0	4.778 - 4.892	4.625	2.00	2-3/8 EUE	43955
	20.0 - 26.0	4.548 - 4.778	4.375	2.50	2-7/8 EUE	43957
6-5/8	20.0	6.049	5.750	3.00	3-1/2 EUE	43965
	20.0 - 24.0	5.921 - 6.049	5.750	4.00	4-1/2 EUE	43966
7	17.0 - 29.0	6.184 - 6.538	6.000	2.50	2-7/8 EUE	43971
				3.00	3-1/2 EUE	43973
	20.0 - 29.0	6.184 - 6.456	6.000	2.00	2-3/8 EUE	43970
				4.00	4-1/2 LTC	43974
7-5/8	24.0 - 26.4	6.969 - 7.025	6.750	2.50	2-7/8 EUE	43976
	29.7 - 33.7	6.765 - 6.875	6.375	2.50	2-7/8 EUE	43975
8-5/8	28.0 - 36.0	7.825 - 8.017	7.375	2.50	2-7/8 EUE	43985
9-5/8	40.0 - 47.0	8.681 - 8.835	8.450	3.00	3-1/2 EUE	43995
10-3/4	40.5 - 55.5	9.760 - 10.050	9.710	4.00	4-1/2 LTC	4391075

NOTE: All pricing includes standard Nitrile trim. Other sizes and connections are available upon request.



2 Cup Version



4 Cup Version