

PERMANENT HYDRAULIC ISOLATION PACKER

The **Permanent Hydraulic Isolation Packer** is a robust production packer capable of handling large amounts of weight hung below the packer. This packer features a large ID for increased flow potential. This packer also has upper and lower centralizing slips which increases its ability to set in deviated sections of wells. This packer uses our proven Permapak components.

The setting equipment for the Permanent Hydraulic Isolation Packer is built into the packer. It requires pressurizing the tubing/casing it is run on once the packer reaches setting depth.

Special Features

- Adjustable setting initiation pressure
- Uses proven Permapak components



Hydraulic Set Packers

Product Specifications

Casing		Recommended Hole Size (inches)	Tool OD (inches)	Packer Bore (inches)	Thread Connections Box Up / Pin Down	Part Number
Size (inches)	Weight (lbs/ft)					
7	17.0 - 26.0	6.276 - 6.538	6.000	4.000	4-1/2 LTC	68570
					4-1/2 BTC	68570-XBLA
	23.0 - 32.0	6.094 - 6.366	5.875	4.000	4-1/2 LTC	68571
					4-1/2 BTC	68571-XBLA
7-5/8	24.0 - 39.0	6.625 - 7.025	6.250	4.000	4-1/2 LTC	68575
					4-1/2 BTC	68575-XBLA
9-5/8	36.0 - 53.5	8.535 - 8.921	8.125	5.000	5-1/2 LTC	68595-XBCC
				5.500	6-5/8 LTC	68595
				6.000	7" LTC	68595-XBCE

NOTE: All pricing includes standard Nitrile trim. Other sizes and connections available upon request.