

TRILOBITE HYDRO ANCHOR

The **Trilobite Hydro Anchor** is a hydraulically-set, retrievable, tubing anchor / catcher featuring D&L's patent pending slip / cone design. The Trilobite Hydro Anchor utilizes heat-treated steel alloy double-acting slips for maximum holding power in tension or compression. The fully enclosed slips allow for maximum bypass area around the outside of the anchor while maintaining a full open ID through the tubing. This versatile design can be used to route multiple capillary lines or monitoring cables past the anchor and to provide a gas/debris bypass area around the three slips.

The Trilobite Hydro Anchor catcher prevents movement of the tubing during pumping strokes and holds it stationary if it should part. This increases pump efficiency, reduces rod and tubing wear, and keeps tubing and rods from falling into the well in case of a part.

Special Features

- Patent pending, fully enclosed slip/ cone design
- Maximum holding power in tension or compression
- Large flow area around tool
- Full open ID
- Shear release



Product Specifications

Casing		Recommended Hole Size (inches)	Max OD (inches)	Reduced OD (inches)	Tool ID (inches)	Thread Connections Box Up / Pin Down	Part Number
Size (inches)	Weight (lbs/ft)						
5-1/2	14.0 - 23.0	4.670 - 5.040	4.50	3.67	2.44	2-7/8 EUE	31956
7	17.0 - 32.0	6.094 - 6.538	5.75	4.50	3.00	3-1/2 EUE	31973

Anchors